

### Melting of sodium hydroxide dihydrate

IN Yamaoka, Yoshitaka; Koike, Masayuki; Okamoto, Noriaki; Oda, Masao; Miyashita, Masaichi; Kawamura, Shigenobu; Matsui, Etsuo; Nakajima, Masao  
PA Ishikawajima-Harima Heavy Industries Co., Ltd., Japan; Tokuyama Soda Co., Ltd.  
SO Jpn. Kokai Tokkyo Koho, 5 pp.  
PI JP 53120697 19781021 Showa  
AI JP 77-36352 19770331  
DT Patent  
LA Japanese  
AB Aq. NaOH contg. impurities is cooled, the crystd.-out NaOH.2H<sub>2</sub>O is sepd., melted with addn. of H<sub>2</sub>O to contain .ltoreq.46.5% NaOH, and the soln. is indirectly heat-exchanged with compressed cooling gas. Thus, NaOH.2H<sub>2</sub>O 85 kg and H<sub>2</sub>O 4.5 L/h were fed into the stirred 49.2% NaOH soln. in 1 m depth at 15.degree. (warmed by a jacket with water at 50.degree.) to obtain 49.2% NaOH continuously, vs. 51.8% with NaOH.H<sub>2</sub>O crystals below 22.degree. without H<sub>2</sub>O addn.